


MACHINE PARAMETERS



TECHNICAL SPECIFICATION

Model	GIT3200UV	
Head Qty	2—12pcs	
Resolution	Max 720*2400dpi	
Printhead	Ricoh GEN5	Ricoh GEN6
Draft mode	70m ² /h	85m ² /h
Production mode	54m ² /h	68m ² /h
Quality mode	32m ² /h	39m ² /h
Color	K/C/M/Y/LC/LM/W/V (Optional)	
Printing size	0-3200mm	
Printing thickness	0-50mm	
Data interface	USB	
PC	Window 7、Window10	
Printing media	PVC film, 3P cloth ,Fabric , Leather, PVC board, Acrylic, Glass, Wood etc.	
Ink type	Eco-friendly UV-curable ink	
Input format	Adobe Postscript Level 3、PDF、 JPEG、 TIFF、 EPS、 AI	
Curing	High-effect UV LED	
Printer weight	2000KG	
Printer size	5800*1690*1600mm	
Power	6.5kw	
Power requirement	Single phase AC 208-240V±10%、 50/60Hz、 32A	
Environment	Independent, clean, low dust, less light, good ventilation workshop	
Temperature	18°C ~ 30°C (64°F ~ 86°F)	
Humidity	30% ~ 70% (no condensation)	
Ventilation	It is recommended to use an overhead exhaust fan 600 cfm	

Above specifications are subject to change without prior notice.

>>> Outstanding Compatibility Reinforced Power <<<

GIBSON



>>> Digital Inkjet Printing Solution Supplier-UV Hybrid Series<<<

GIT 3200 UV Hybrid Printer

>>> Gibson Image Technology (Guangdong) Co.,Ltd <<<



Add Corso Traiano 168 a
10127 Torino - Italy
Tel +39 011 317 24 42
Web www.gibsonprinter.it
Mail info@gibsonprinter.it





PRINTER DETAILS

Fully automatic intelligent engine

- THK high precision silent guide rail
- 1.7m/s linear motor
- Automatic height measurement
- High sensitivity intelligent collision avoidance device
- Supports a maximum of 16 heads with high compatibility

Super stable all steel frame

- All bearing parts are not welded, special steel to ensure long-term operation without deformation
- Levelness support platform printing is nearly perfect

Ultimate parts combination

- Japanese brand reducer + self-developed motion control system = perfect stepping
- Ultra lightweight and extensible platform (750mm), easy to loading flat materials

PLC control system

- The senior team independently developed intelligent vacuum adsorption control and intelligent touch control system, greatly reducing the physical accessories

Unparalleled soft media output

- Continuous 200 meters of all kinds of soft material printing, high-speed output wrinkle-free
- Double roll can be printed at the same time, different feeding devices to achieve easy feeding

Industrial rigid media output

- Industrial horizontal and vertical positioning system, intelligent correction design to ensure the full print extremely accurate

PRINTING MODE



White Upper-layer



Image A-White-Image B



5 layers printing



Embossed printing



White Under-layer



White-color-varnish

APPLICATIONS



Background wall



Advertising light box



Car Stickers



Decorative pattern



Decorative painting



Mouse



Subareas screens



Large billboard